


















KINDS AND DIMENSIONS / 제품종류와 치수안내 (주문표)

Shift Chain E-Type	Pitch	Bending Radius R 	Weight kg/m	Speed m/sec	Temperature °C	Clearance 				Frame style	Divider possible with frame
						A	B	C	D		
ST044E .035	44	70, 90, 120, 150	1.03	10	-30 ~ +130	56	38	35	24.5		
ST044E .055	44		76			38	55	24.5			
ST044E .075	44		96			38	75	24.5			
ST044E .100	44		121			38	100	24.5			
ST055E .050	55	100, 125, 150, 200	1.36	10	-30 ~ +130	71	52	50	38.5		
ST055E .075	55		96			52	75	38.5			
ST055E .100	55		121			52	100	38.5			
ST055E .125	55		146			52	125	38.5			
ST055E .150	55		171			52	150	38.5			
ST072E .050	72	120, 145, 200, 250, 300	2.03	10	-30 ~ +130	82	66	50	44		
ST072E .075	72		107			66	75	44			
ST072E .100	72		132			66	100	44			
ST072E .125	72		157			66	125	44			
ST072E .150	72		182			66	150	44			
ST095E .100	95	150, 200, 230, 280, 400	3.55	10	-30 ~ +130	138	82	100	55		
ST095E .125	95		163			82	125	55			
ST095E .150	95		188			82	150	55			
ST095E .175	95		213			82	175	55			
ST095E .200	95		238			82	200	55			
ST120E .150	120	200, 250, 300 350, 400, 500	5.79	10	-30 ~ +130	192	108	150	76		
ST120E .200	120		242			108	200	76			
ST120E .250	120		292			108	250	76			
ST120E .300	120		342			108	300	76			
ST150E .200	150	305, 405, 505, 605	8.16	10	-30 ~ +130	246	141	200	110		
ST150E .250	150		296			141	250	110			
ST150E .300	150		346			141	300	110			
ST150E .350	150		396			141	350	110			
ST150E .400	150		446			141	400	110			



ST044E-view

