



TRS-V Series Dimension Table



Model No.	Assembly(mm)				Block(mm)							Rail(mm)								
	H	W2	E	W	B	J	L	L1	QX l	T1	Oil Hole	N	W1	H1	ØD	h	Ød	F		
	TRS15VS	24	9.5	3.2	34	26	39.3	22.9	26	55.9	39.5	M4X5	5.5	M4X0.7	7	15	13	7.5	6	4.5
TRS15VN						47.8	27.8		M5X5	4.5	M6X1	14	20	16.5	9.5	8.5	6			
TRS20VS	28	11	4.6	42	32	66.7	46.7		M6X6	4.5	M6X1	14	23	20	11	9	7			
TRS20VN						56.2	35.2		M8X8	8	M6X1	14	28	23	14	12	9			
TRS25VS	33	12.5	5.8	48	35	80	59		M8X8	8	M6X1	14	34	26	14	12	9			
TRS25VN						66.4	40.4		M10X15	10.5	PT1/8	12.5	45	32	20	17	14			
TRS30VS	42	16	7	60	40	95.3	69.3		M10X15	10.5	PT1/8	12.5	45	32	20	17	14			
TRS30VN						106	80													
TRS30VL						108	79													
TRS35VN	48	18	7.5	70	50	108	79													
TRS35VE						152	123													
TRS45VN	60	20.5	8.9	86	60	124.5	90.5													

Model No.	Rating Load (kgf)		Static permissible moment of load				Weight		
	C	Co	My(kgf-mm)		Mz(kgf-mm)		Block (kg)	Rail (kg/m)	
			Single Block	Double Block	Single Block	Double Block			
TRS15VS	908	1471	10,957	6,420	33,531	6,420	33,531	0.07	1.32
TRS15VN	1206	2206	16,436	14,884	70,960	14,884	70,960	0.13	
TRS20VS	1398	2140	21,615	10,700	59,798	10,700	59,798	0.11	2.28
TRS20VN	1896	3307	33,404	26,459	126,998	26,459	126,998	0.18	
TRS25VS	1943	3002	34,826	18,725	97,890	18,725	97,890	0.18	3.17
TRS25VN	2581	4503	52,239	43,407	207,324	43,407	207,324	0.3	
TRS30VS	2697	3962	55,442	26,950	154,224	26,950	154,224	0.37	4.54
TRS30VN	3807	6483	90,722	74,970	355,321	74,970	355,321	0.65	
TRS30VL	4098	7203	100,803	93,100	438,966	93,100	438,966	0.74	6.27
TRS35VN	5090	8346	142,722	106,070	519,799	106,070	519,799	0.98	
TRS35VE	6667	12274	209,885	233,977	1,070,533	233,977	1,070,533	1.54	10.4
TRS45VN	6758	10887	248,758	158,011	782,271	158,011	782,271	1.71	